



## Front Cargo Rack Installation Instructions

### Contents:

Qty	Item
1	Rack
1	Grill guard
2	Bolt, 5/16 x 2 1/4 Socket Head
2	Bolt, 5/16 x 2 1/2 Hex Head
2	Bolt, 5/16 x 1 1/2 Hex Head
6	Nut, 5/16 Nylock
6	Washer, 5/16 Flat
4	Washer, 5/16 Curved
2	Rubber edge trim, 4" inches long



### Instructions:

1. Remove front cage bolts. If you have a windshield remove the plastic catches at the bottom that hold the windshield when it is folded down. (Upper left photo)
2. Place the grill guard on the front bumper. If the bumper brackets are not pointing down, turn the guard around.
3. Insert the two ends on the top of the guard into the two tubes on the bottom of the rack. (Upper right photo)
4. Attached the rear rack brackets to the cage using the new 5/16 x 2 1/4" socket head bolts, two flat washers and two nuts. (Middle left photo)
5. Fasten the rack to the grill guard with two 5/16 x 1 1/2" bolts, four curved washers and two nuts. (Middle right photo)
6. Fasten the grill guard to the bumper with two 5/16 x 2 1/2" bolts, four flat washers and two nuts. (Lower left photo).
7. If you have a windshield, place the rubber edge trim on the windshield's top edge where it contacts the rack when folded down. (Lower right photo).

