

Model 5210 Specifications

for ages 13 +

ENGINE TYPE	Single cylinder, 208cc,	FRONT SUSPENSION	Double A-arm with	SEAT TO PEDALS	39" - 41"
	air cooled, 4 cycle		damped shocks	WHEEL BASE	54.7"
POWER (BHP @ RPM)	≈ 6.45 @ 3573	REAR SUSPENSION	Swing arm with	DIMENSIONS	82"L x 48"W x 52.7"H
TORQUE (Ft-lbs @ RPM)	$\approx 9.48 @ 3073$		damped shocks	PARKING BRAKE	Pedal latch style
STARTING SYSTEM	Electric start with recoil	STEERING	Rack and Pinion	HEADRESTS	Yes
	backup plus manual chok	ke FRAME	Heavy guage jig welded	SEATS	Adjustable driver, fixed
AIR FILTRATION	Dual element		1.125" main frame		passenger buckets
EXHAUST SYSTEM	Muffler with heat shield	REAR AXLE	7/8" Hardened alloy steel	SAFETY FEATURES	3-point shoulder / lap
FUEL CAPACITY	.67 gallon	FINISH	Baked powder coat		belts with retractor, on
OIL CAPACITY	16 oz.	BRAKES	Rear single hydraulic disc		engine and in dash
SPARK PLUG	NGK F6RTC	MAX SPEED	Up to 24 mph		engine stop switches
DRIVE	Dual wheel drive CVT	FUEL CONSUMPTION	Up to 50 mpg		plus keyswitch,
CHAIN SIZE	#420 1/2" Pitch	CURB WEIGHT	335 lbs.		1.125" full brush bars, whip
FRONT TIRES	16 x 6 - 8	VEHICLE CAPACITY	400 lbs. (Driver,		flag, pedal latch style
REAR TIRES	18 x 9.5 - 8		passenger & gear)		parking brake

WARRANTY INFORMATION

- 3 years: Engine Warranty by LCT.
- 90 days: Frame, Brush Bars, Spindles, Seat Frame.
- 30 days: All other components.

