



Powered by 653cc gasoline engine and 24KW/48V electric motor

Gasoline engine powers vehicle for longer range or when you need more power

Electric motor powers vehicle for short distances or when you want to be totally silent you can run exclusively on the batteries


4-wheel drive operation powers vehicle with both the electric motor and the gasoline engine simultaneously

4-wheel brakes: disc front and drum rear with regenerative braking

1200 lb. towing capacity

The most popular hunting accessories come standard Locking differential to help get you through rough terrain Total range of up to 130 miles (see mileage estimate chart)







all shown accessories come standard

Specifications

MUTUK TTPE	48V DC / 4-Stroke UHV V-tWIII
MOTOR SIZE	24kw at 46 ft. lbs of torque with
	500 amn Curtis controller /

653cc Subaru

SPEED Up to 22 mph* FUEL CONSUMPTION Up to 18 mpg*

RANGE ELECTRIC: up to 10 miles*

GAS: up to 90 miles*

STARTING Keyed ignition (electric motor) 12V electric keyed ignition

BATTERY 4 -12V US Battery 155 amp hour

deep cycle batteries (48V drive power) / 12V / 360 cca utility

class (starting)

ON-BOARD CHARGER Delta Q. 48V. sealed, solid state, UL and CE compliant

SPARK PLUG NGK BPR4FS

FUEL CAPACITY 5.0 gallons **ALTERNATOR** Converter 20 amps / 30 amp LOW OIL SHUTDOWN Oil pressure warning light **TRANSMISSION** Direct drive / CVT automatic

DIFFERENTIAL Manual lock differential **TRANSAXLE** H-12 DANA gearbox / gear drive Dana-Spicer oil-filled transaxle

DRIVE 2 Wheel drive / switch engaged on demand, 4-wheel drive

FRONT SUSPENSION Double A-arm front with up to 3" travel, coil over gas

reservoir shock absorbers

REAR SUSPENSION Articulated rear swing arm, quad adjustable shocks

with 3" travel

BRAKE SYSTEM Hydraulic disc front, Hydraulic drum fear

FRONT/REAR TIRES 25" x 11" x 12" heavy duty

6 ply rated

DIMENSIONS 142" L x 48" W x 75" D

WHEEL BASE 104"

TURNING RADIUS 19.5' inside radius

DRY WEIGHT 1787 lbs.

SHIPPING WEIGHT 1787 lbs. (ships uncrated)

BED MATERIAL Steel (no flipseat) BED DIMENSIONS 34" L x 42" W x 10" D BED CAPACITY 8.26 cu.ft. / 400 lbs.

REAR FLIP SEAT Not an available option

TOWING CAPACITY 1200 lbs. **VEHICLE CAPACITY** 1500 lbs. **PARKING BRAKE** Hand operated

HEADRESTS Yes **UNDER SEAT STORAGE** Yes

WARRANTY Engine: 5 year by SUBARU

All other components: 1 Year by ASW **SPECIAL FEATURES** 3pt Lap/Shoulder Belts for Driver

and Passenger, 35W Headlights. Polyurethane Powdered Coat Paint, 2" Rear Receiver Hitch, Dump Bed.

Bench Seating, Welded Steel Frame INCLUDED ACCESSORIES Hard top, windshield, CV guard, skid plate, 2500 Lb. capacity front winch,

2" front receiver, front hood rack

powered by SUBARI



Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances. Specifications are subject to change without notice.