



48 Volt high efficiency motor for reliable power

Regenerative braking on the motor to facilitate deceleration and help recharge the batteries

Sealed solid state Delta-Q charger on board with dash mounted charge meter

6 - 8 Volt Trojan Deep Cycle Batteries

500 amp Curtis controller for efficient power distribution

Dual mode switch for speed control or extended range

2 inch rear receiver hitch

Available in red, green, white*, black* or camo*

THIS UNIT CAN BE ORDERED AS AN "S" MODEL (LMLSVS)
unit shown with optional accessories



When ordered, an "S" variation will come with a steel bed and our patented rear flip seat kit. Go from dump capable steel bed to 2 person rear seat with safety belts in about 10 seconds.



★
**WINDSHIELD
COMES
STANDARD**

unit shown with optional hard top and folding windshield

Specifications

MOTOR TYPE	48V DC	TRANSAXLE	H-12 Shafer/DANA gearbox	BED CAPACITY	9.25 cu.ft. / 400 lbs.
MOTOR SIZE	24kw at 46 ft. lbs of torque with 500 amp Curtis controller	DRIVE	2 Wheel drive	REAR FLIP SEAT	Available when ordered as an "S" model
SPEED	Up to 22 mph** (Up to 10 mph in M2)**	FRONT SUSPENSION	Double A-arm featuring adjustable shocks with up to 3" travel	TOWING CAPACITY	1100 lbs.
FUEL CONSUMPTION	N/A	REAR SUSPENSION	Articulated rear swing arm, quad adjustable shocks with 3" travel	VEHICLE CAPACITY	900 lbs.
RANGE	Up to 38 miles (in M2)**	BRAKE SYSTEM	6.25" Dual rear drum, with regenerative braking	PARKING BRAKE	Hand operated
STARTING	Keyed on/off switch	FRONT/REAR TIRES	22 x 11 - 10"	HEADRESTS	Yes
BATTERY	6 - 8 volt Trojan T-875 Deep Cycle Batteries	DIMENSIONS	106" L x 47" W x 74" D	UNDER SEAT STORAGE	Yes
ON-BOARD CHARGER	Delta Q, 48V, sealed, solid state, UL and CE compliant	WHEEL BASE	71"	WARRANTY	1 Year by ASW
SPARK PLUG	N/A	TURNING RADIUS	7.5' inside radius	SPECIAL FEATURES	3pt lap/shoulder belts for driver and passenger, 35W headlights, on-board charger, 2" rear receiver Hitch, welded steel frame, 12V auxiliary outlet for accessories
FUEL CAPACITY	N/A	DRY WEIGHT	1250 lbs.	LSV ADDITIONAL FEATURES	Listed with NHTSA, meets FMVSS 500 specs, turn signals, horn, polycarbonate shatter resistant windshield
ALTERNATOR	Converter/20 amps	SHIPPING WEIGHT	1360 lbs.		
LOW OIL SHUTDOWN	N/A	BED MATERIAL	Structural foam "Poly Bed" with stake pockets		
TRANSMISSION	Direct drive	BED DIMENSIONS	35.25" L x 41.5" W x 11" D		
DIFFERENTIAL	Open differential				

* White, black or camo available at additional cost.

** Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances. Specifications are subject to change without notice.